



Declaration of Performance (DoP)

| | |
|---|---|
| No. F3-CPR-130823 | |
| Product Type: | Roomheaters fired by solid fuel |
| Type, batch or serial number: | Jøtul F 3 |
| Intended use of the product: | Roomheater burning solid fuel without water supply |
| Name and Address of the manufacturer: | Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no |
| AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i> | System 3 |
| Notified body: NB-No: Test report no: | Rhein-Ruhr Feuerstätten Prüfstelle 1625 RRF- 40 06 1131 |
| Declared performance: | |
| Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 |
| Essential characteristics | Performance |
| Fire safety Reaction to fire Distance to combustible materials | A1 Minimum distances, in mm Rear = 350 Sides = 600 Corner = 350 Front = 800 <i>See also the installation instructions</i> |
| Risk of burning fuel falling out | No |
| Emission of combustion products | CO [0,05 %] NOx [31 mg/m ³] OGC [7 mgC/m ³] PM [59 mg/m ³] |
| Surface temperature | Pass |
| Electrical safety | - |
| Cleanability | Pass |
| Maximum water operating pressure | - |
| Flue gas temperature at nominal heat output | T [356°C] |
| Mechanical resistance (to carry a chimney/flue) | NPD |
| Thermal output Normal heat output Room heating output Water heating output | 6 kW - kW -*kW |
| Energy efficiency | η [78%] |

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, August 23rd 2013

(Place and date of issue)

Tom J. Berglind

(Signature)